



نام محصول : مانیتور صنعتی

نوع محصول : Industrial monitor

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : PV-244K-I

KEY FEATURES

- HD: 1920 * 1080 is higher than the ordinary monitor resolution
- Boot on the lower left screen automatically detect the resolution of the input signal is high or low, resolution with data
- Clear: exquisite realistic, true color, showing off is my true colors
- Bright: quality promotion, to be better
- Use industrial screen, high brightness, high contrast
- Standard regulated power supply with high precision, for industrial
- Equipment design, support x 365 day uninterrupted work 24 hours a day
- Using 10 bit figure like chip processing technology, high pixel progressive scan, image quality and exquisite realistic
- Support intelligent 3 d noise reduction, to eliminate the ghosting, dynamic brightness, contrast color optimization techniques
- Used the world's leading liquid crystal drive scheme, a precise reduction front-end signal, strong sense of reality
- LCD has a small volume, low energy consumption, zero radiation, image stabilization, no influence on the eyes, natural health
- 5ms speed response, to avoid the image phenomenon of trailing in the high-speed running.

Display

Model	LED24
Panel size	24 inch
Resolution	1920*1080(compitable3840*2160/30HZ)
Display ratio	16:9
Brightness	300cd/m ² (Central point ,typical value)
Contrast	3000:1
Visual angle	89/89/89/89 (Typ.)(CR≥10)
Response time	5ms(Gray To Gray)
Depth of color	16.7M

Function attribute

Control mode	Panel
--------------	-------

Interface

Input power	12V/4A
Input interface	HDMI*1、VGA*1、USB*1、Audio output*1

Power dissipation

Total consumption	24W
-------------------	-----

Construction

Color	black
Material	Frame retardant plastic
Overall dimension	542*320*44mm (excluding foot height 80mm)
Packing Size	600*110*400mm



Mounting method	Base wall mounted(100mm*100mm)
Gross weight/Net weight	2.8kg/3.7kg
Out packing size	610*580*420mm 5pcs/ctn
Out packing weight	19.5kg

Working environment

Working environment temperature	Suitable temperature 20°C
Working environment humidity	10%-90%RH

