



نام محصول : ویدیو وال

نوع محصول : Video wall

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : PV-654K-W0.8

KEY FEATURES

- Using original industrial grade IPS (DID) LCD splicing panel.
- Adopt direct down LED backlight technology and shimity of screen brightness.
- With 1920×1080/3840×2160 resolution, it can restore ultra-high resolution original image display by splicing.
- Adopt high heat dissipation body design, support 7×24 hours continuous work, long service life.
- Adopt module unit assembly method, support embedded, wall-mounted, hanging and other installation methods. no out film filter, which can ensure the high uniform.

Product Specifications

Product Line	LED Splicing Screen
Splicing thickness	0.8MM
Screen size	65 inch
Appearance color	Black

Input/output interface

USB input	1 x USB2.0, Max 480Mbps
Audio speaker output	Built-in speaker interface, supports up to 8Ω 10W dual channel speaker output - Support 1 HDMI input, support version 2.0, maximum support 3840X2160@60Hz input - Support 1 channel DVI signal signal input, the maximum support 3840X2160@60Hz input.
Signal Input	- Support RJ45 input and output, access to infrared receiver head and RS232 for device control and debugging. - 1-channel VGA input, 1-channel AV input Support 1-way USB multimedia video, picture, text file view, program upgrade - Support image 180-degree flip

Electrical performance of the whole machine

Power input	65 inches
LED Panel	MP4955T-163V 1000
Input	100-240V~,50~60Hz,3.8A,Max
DC Output	12V=4A
Power consumption of the whole machine	65 inches: 159w

Main Hardware

Memory	All hardware architecture, no memory, no storage
Built-in memory	Not supported
Memory Expansion	Not supported
WiFi	Not supported
Operating System	All hardware architecture, no CPU and no OS
Decoding Resolution	Maximum resolution 3840X2160 60Hz

Display performance parameters

Product Model	PV-654k-W0.8
Backlight Type	LED
Display size(mm)	L1432.3x W808.5



Physical resolution rate	4K (3840 x 2160), UHD
Peak brightness of the whole machine	500cd/m ² ±30
Dynamic Contrast Ratio	4000: 1
Visual View	89/89/89/89 (Typ.)(CR≥10)
Screen Ratio	16:9
Display color	16.7M (8-bit)
Surface treatment	matte surface
Operating frequency	60Hz

Structure size (unit: mm)

Overall size of the machine (Length × Height × Thickness)	L1440.3 x H816.5 x W72.4 (W69.4 for removing the handle)
Outer box packing size (Length × Height × Thickness)	L1530 x H160x W907
Net weight of bare machine (KG)	18.2
Gross weight of the whole machine (KG)	20 (single unit load)

