



نام محصول : سویچ شبکه

نوع محصول : PoE Switch

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : SRS-48G04F-P

KEY FEATURES

48 Gigabit RJ45 PoE Port	Realtek Processor
4 Gigabit SFP Uplink Port	PoE Distance up to 120m
1200 Watt	Metal Case
104Gb Internal Bandwidth	

interface

Total Port	52 Ports
Max POE Output	1200Watt
POE Port Control	Texas Instruments Chipset
Fast RJ45 POE Port	N/A
Gigabit RJ45 POE Port	48 Port
Fast RJ45 Uplink Port	N/A
Gigabit RJ45 Uplink Port	N/A
Gigabit SFP Uplink Port	4
Combo Uplink Port	N/A

Network Performance

Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3ab, IEEE802.3af, IEEE802.3at(Up to 30Watt), IEEE802.3bt
Protocols	CSMA/CD
Router	N/A
Speed	Ethernet 10Mbps (half duplex), 20Mbps (full duplex); 10BASE-T: 14,880bps/port Fast Ethernet 100Mbps (half duplex), 200Mbps (full duplex); 100BASE-TX:14,880bps/port Gigabit Ethernet 1000Mbps (half duplex), 2000Mbps (full Duplex); 1000BASE-TX: 1488000bps/port
Cabling	10Base-TX: Cat 5 or above (120m) POE=120M 100Base-TX: Cat 6 UTP (100m) POE=120M 1000Base-TX: Cat 6 UTP or above (100m) POE=120M
Bandwidth	104Gb Internal Bandwidth
MAC Table	512Kb
Auto MDI-MDIX	Yes, All Port
Console	Yes – Web & RS232(Talent Support) Layer2 Management
Transfer Pattern	Store & forward

Hardware

Processor Type	Realtek
LED Panel	POE Activity / Data Activity
Main Board	Double Layer
Case	Metal Case
Mounting	Rackmount

PD'S

IP Camera	Yes
IP Phone	Yes
(+)5/4,(-)8/7	Optional
(+)2/1,(-)6/3	Yes



General

IP Rating	IP51
Web Language	English
Dimension	440*338*45 mm
Weight	4.5 Kg
Storage Temp	-20°~+60°C / 10%~90%RH
Operation Temp	-15°~+50°C / 10%~90%RH
Radiation Electromagnetic	EN55016

Status

LED	Ethernet Interfaces 1000 LNK/ACT (Green), 10/100 LNK/ACT (Green) PoE Ethernet Interfaces, PoE-in-Use (af/at/bt) 1000 LNK/ACT (Orange), 10/100 LNK/ACT (Green)
-----	--

Power Supply

Power	200~240V AC, 50~60Hz
Redundant	N/A
LED Power	Yes
Power Cable	Available

Guarantee

Product Guarantee	3 Year Platinum Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)

