



نام محصول : سویچ شبکه

نوع محصول : PoE Switch

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : SRS-48G04XF-P

## KEY FEATURES

48 Gigabit RJ45 PoE Port	Realtek Processor
4 SFP+ (10Gigabit) Uplink Port	PoE Distance up to 120m
1200 Watt	Metal Case
176Gb Internal Bandwidth	

## interface

Total Port	52 Ports
Max POE Output	1200Watt
POE Port Control	Texas Instruments Chipset
Fast RJ45 POE Port	N/A
Gigabit RJ45 POE Port	48 Port
Fast RJ45 Uplink Port	N/A
Gigabit RJ45 Uplink Port	N/A
Gigabit SFP Uplink Port	4
Combo Uplink Port	N/A

## Network Performance

Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3ab, IEEE802.3af, IEEE802.3at(Up to 30Watt), IEEE802.3bt
Protocols	CSMA/CD
Router	N/A
Speed	Ethernet 10Mbps (half duplex), 20Mbps (full duplex); 10BASE-T: 14,880bps/port Fast Ethernet 100Mbps (half duplex), 200Mbps (full duplex); 100BASE-TX:14,880bps/port Gigabit Ethernet 1000Mbps (half duplex), 2000Mbps (full Duplex); 1000BASE-TX: 1488000bps/port
Cabling	10Base-TX: Cat 5 or above (120m) POE=120M 100Base-TX:Cat 6 UTP(100m) POE=120M 1000Base-TX: Cat 6 UTP or above (100m) POE=120M
Bandwidth	176Gb Internal Bandwidth
MAC Table	2Mb
Auto MDI-MDIX	Yes All Port
Console	Yes – Web & RS232(Talent Support) Layer3 Management
Transfer Pattern	Store & Forward

## Hardware

Processor Type	Realtek
LED Panel	POE Activity / Data Activity
Main Board	Double Layer
Case	Metal Case
Mounting	Rackmount

## PD'S

IP Camera	Yes
IP Phone	Yes
(+)5/4,(-)8/7	Optional



(+)2/1,(-)6/3 Yes

#### General

IP Rating	IP51
Web Language	English
Dimension	443*460*45 mm
Weight	4.5 Kg
Storage Temp	-20°~+60°C / 10%~90%RH
Operation Temp	-15°~+50°C / 10%~90%RH
Radiation Electromagnetic	EN55016

#### Status

LED	Ethernet Interfaces 10,000 LNK/ACT (Green), 10/100/1000 LNK/ACT (Green) PoE Ethernet Interfaces, PoE-in-Use (af/at/bt) 1000 LNK/ACT (Orange), 10/100 LNK/ACT (Green)
-----	---

#### Power Supply

Power	200~240V AC, 50~60Hz
Redundant	N/A
LED Power	Yes
Power Cable	Available

#### Guarantee

Product Guarantee	3 Year Platinum Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)

